

CO-sinusUPS-600W-LCD

Inverter with UPS function (600VA / 500W)



■ Features:

- Friendly interface
- Compact size
- Low price



ELECTRICAL SPECIFICATION

MODEL	CO-sinusUPS-600W-LCD
-------	----------------------

OUTPUT

Rated Power	500W (600VA)
Output Voltage Range (inverter mode)	150 ÷ 255VAC (±5VAC)
Output Voltage Range (bypass mode)	203 ÷ 238VAC (±5VAC)
Frequency (battery mode)	50Hz ± 0.1Hz
Voltage waveform	True sinus
Transfer time	< 10ms

INPUT

Output Voltage Range (inverter mode)	100 ÷ 264VAC (±5VAC)
Output Voltage Range (bypass mode)	203 ÷ 238VAC (±5VAC)
Frequency Range	45 ÷ 65Hz

BATTERIES

CHARGING CURRENT (MAX.)	10A/20A/Max.
Type and Capacity Of Batteries	GEL / AGM / ACID; 12V/55-200Ah

WORKING ENVIRONMENT

Working Temperature	0°C ÷ 40°C
Working Humidity	20 ÷ 90% RH non-condensing
Noise Level	< 40dB (1m)

OTHERS

Dimensions	290.35 x 257.5 x 120mm (dł. x wys. x szer.)
Weight	7.6 kg

EAN Code



5 902135 124086

MECHANICAL SPECIFICATION

