

CO-sinusUPS-400W

Pure sine wave inveter (400W)



■ Features:

- Easy user interface
- Compact size
- Low price



ELECTRICAL SPECIFICATION

MODEL	CO-sinusUPS-400W
OUTPUT	
<i>Rated Power</i>	400W
<i>Output voltage range (AC mode)</i>	200-250VAC (±7VAC)
<i>Output voltage (Battery mode)</i>	220VAC (±10VAC)
<i>Output frequency (Battery mode)</i>	50Hz
<i>Output waveform</i>	Pure sine wave
<i>Transfer time</i>	< 10ms
INPUT	
<i>Voltage Range</i>	155 ÷ 264VAC (±7VAC)
<i>Input frequency</i>	50Hz
BATTERY	
<i>Charging current (max.)</i>	6A
<i>Type and capacity of battery</i>	12V GEL / AGM / WET; 26-100Ah
WORKING ENVIRONMENT	
<i>Working Temperature</i>	0°C ÷ 40°C
<i>Working Humidity</i>	20 ÷ 90% RH non-condensing
<i>Noise level</i>	< 40dB (1m)
OTHERS	
<i>Dimensions</i>	246 x 205 x 104mm (L x W x H)
<i>Weight and box dimension</i>	6 kg; 305 x 265 x 180 mm

EAN code



5 49 021 354 24 079 1

MECHANICAL SPECIFICATION

